

Technical Data Sheet

93800050452_V07_en_GB

Voltage / Frequency

Cooling water temperature (in / out)

NOx emissions (dry, 5 % O₂)

Mixture cooler 1st stage water temperature (in)

Mixture cooler 2nd stage water temperature (in)

Exhaust gas temperature

Catalytic converter

Special equipment

Altitude above sea level

Combustion air temperature

Relative combustion air humidity

Standard specifications and regulations

MTU 16V4000 GS

GG16V4000A1



V / Hz	6300	/	50
°C		78 / 90	
mg/m ³ i.N.		< 500	
°C		43	
°C		416	
		not included	
m / mbar	100	/	1000
°C		25	
%		30	

Energy balance	%	100	75	50
Electrical Power ^{2) 3)}	kW	2028	1521	1014
Energy input ^{4) 5)}	kW	4573	3511	2455
Thermal output total ⁶⁾	kW	965	708	477
Thermal output engine (block, lube oil, 1st stage mixture cooler) ⁶⁾	kW	965	708	477
Thermal output mixture cooler 1st stage ⁶⁾	kW			
Thermal output mixture cooler 2nd stage ⁶⁾	kW	127	91	61
Exhaust heat (120 °C) ⁶⁾	kW	(936)	(787)	(599)
Engine power ISO 3046-1 ²⁾	kW	2080	1565	1051
Generator efficiency at power factor = 1	%	97.5	97.2	96.4
Electrical efficiency ⁴⁾	%	44.3	43.3	41.3
Total efficiency	%	85.9	85.9	85.1
Power consumption ⁷⁾	kW			

Combustion air / Exhaust gas

Combustion air volume flow ¹⁾	m ³ i.N./h	7748	5841	4002
Combustion air mass flow	kg/h	10006	7543	5168
Exhaust gas volume flow, wet ¹⁾	m ³ i.N./h	8002	6036	4138
Exhaust gas volume flow, dry ¹⁾	m ³ i.N./h	7406	5579	3819
Exhaust gas mass flow, wet	kg/h	10342	7801	5349
Exhaust temperature after turbocharger	°C	416	449	483

Reference fuel ⁸⁾

Natural gas			CH ₄ >95 Vol.%
Sewage gas			not applicable
Biogas			not applicable
Landfill gas			not applicable

Fuel requirements ⁹⁾

Minimum methane number	MN		80
Range of heating value: design / operation range without power derating	kWh/m ³ i.N.		10.0 - 10.5 / 8.0 - 11.0

Exhaust gas emissions ^{5) 8)}

NOx, stated as NO ₂ (dry, 5 % O ₂)	mg/m ³ i.N.	< 500
CO (dry, 5 % O ₂)	mg/m ³ i.N.	< 1000
HCHO (dry, 5 % O ₂)	mg/m ³ i.N.	< 102
VOC (dry, 5 % O ₂)	mg/m ³ i.N.	

Otto-gas engine, lean burn operation with turbocharging

Number of cylinders / configuration		16	/	V
Engine type			16V4000L64	
Engine speed	1/min		1500	
Bore	mm		170.0	
Stroke	mm		210.0	
Displacement	dm ³		76.3	
Mean piston speed	m/s		10.5	
Compression ratio			14.0	
BMEP at nominal engine speed min-1	bar	21.8		
Lube oil consumption ¹⁰⁾	dm ³ /h	0.35		
Exhaust back pressure min. - max. after module	mbar - mbar		30 - 60	

Generator

Rating power (temperature rise class F) ¹¹⁾	kVA		3255
Insulation class / temperature rise class			F / F
Winding pitch			2/3
Protection			IP 23
Max. allowable p.f. inductive (overexcited) / capacitive (underexcited) ¹²⁾			0.8 / 0.95
Voltage tolerance / frequency tolerance	%		± 10 / ± 5

Engine cooling water system

Coolant temperature (in / out), design	°C	78 / 90	
Coolant flow rate, constant ^{13) 14)}	m ³ /h	74.9	
Pressure drop, design ¹⁴⁾	Cv value ^{13) 15)}	bar / m ³ /h	3.11
Max. operation pressure (coolant before engine)	bar		6.0

Exhaust gas heat exchanger (EGHE)

Exhaust gas temperature (out)	°C		
Coolant temperature (in / out), design	°C		
Coolant volumetric flow, constant ^{13) 14)}	m ³ /h		
Pressure drop, design ¹⁴⁾	Cv value ^{13) 15)}	kPa / m ³ /h	/
Min. coolant flow rate / min. operation gauge pressure	m ³ /h / bar		/
Max. operation pressure (coolant water)	bar		

Technical Data Sheet

93800050452_V07_en_GB

MTU 16V4000 GS

GG16V4000A1



Mixture cooler 1st stage, external				
Coolant temperature (in / out), design	°C			
Coolant volumetric flow, design, constant ^{13) 14)}	m³/h			
Pressure drop, design ¹⁴⁾	Cv value ^{13) 15)}	bar / m³/h	/	
Min. coolant flow rate / min. operation gauge pressure	m³/h / bar		/	
Max. operation pressure before mixture cooler	bar			
Mixture cooler 2nd stage, external				
Coolant temperature (in / out), design	°C	43 / 46.5		
Coolant volumetric flow, design, constant ^{13) 14)}	m³/h	34.3		
Pressure drop, design ¹⁴⁾	Cv value ^{13) 15)}	bar / m³/h	0.36	/ 58.4
Max. operation pressure before mixture cooler	bar		6	
Heating circuit interface				
Engine coolant temperature (in / out), design	°C			
Heating water temperature (in / out), design	°C			
Heating water flow rate, design ^{14) 16)}	m³/h			
Pressure drop, design ¹⁴⁾	Cv value ^{15) 16)}	bar / m³/h	/	
Max. operation gauge pressure (heating water)	bar			
Room ventilation				
Genset ventilation heat ¹⁷⁾	kW		128	
Inlet air temperature: (min./design/max.)	°C		20 / 25 / 30	
Min. engine room temperature ¹⁸⁾	°C		15	
Max. temperature difference ventilation air (in / out)	K		20	
Min. supply air volume flow rate (combustion + ventilation) ¹⁹⁾	m³ i.N./h		26000	
Gearbox				
Efficiency	%	100	75	50
Starter battery				
Nominal voltage / power / capacity required	V / kW / Ah		24 / 2 x 9 / --	
Filling quantities				
Lube oil for engine	dm³		250	
Coolant in engine	dm³		270	
Coolant in mixture cooler	dm³		25	
Heating water for plate heat exchanger ²⁰⁾	dm³			
Lube oil for gearbox	dm³			
Gas regulation line				
Nominal size / gas pressure min. - max.	DN / mbar - mbar	100	/	180 - 250
Engine sound level ²¹⁾ (1 meter distance, free field) +3 dB(A) for total A-weighted level tolerance				
Frequency	Hz	63	125	250 500
Sound pressure level	dB	84.8	90.5	90.0 93.0
Frequency	Hz	1000	2000	4000 8000
Sound pressure level	dB	92.5	91.8	99.2 101.4
	Lin dB	104.8		
Sum of pressure levels	dB A	104.4		
Sound power level	dB	124.1		
Undamped exhaust noise ²¹⁾ (1 meter distance to outlet within 90°, free field) +3 dB(A) for total A-weighted level tolerance				
Frequency	Hz	63	125	250 500
Sound pressure level	dB	113.8	121.5	110.9 107.3
Frequency	Hz	1000	2000	4000 8000
Sound pressure level	dB	99.5	98.7	95.3 82.5
	Lin dB	122.7		
Sum of pressure levels	dB A	110.0		
Sound power level	dB	122.9		
Dimensions (aggregate)				
Length	mm		~ 5900	
Width	mm		~ 2100	
Height	mm		~ 2300	
Gross weight (dry weight)	kg		~ 19750 (~ 19000)	
Power derating				
Altitude			specific to the project	
Combustion air temperature			specific to the project	
Mixture cooler coolant temperature (in)			specific to the project	
Methane number			specific to the project	

Systems and consumables have to conform to the following actual company standards: A001067

- 1) Normal cubic meter at 1013 mbar and T = 273 K
- 2) Prime power operation will be designed specific to the project
- 3) Generator gross power at nominal voltage, power factor = 1 and nominal frequency
- 4) According to ISO 3046 (+ 5 % tolerance), using reference fuel used at nominal voltage, power factor = 1 and nominal frequency
- 5) Emission values during grid parallel operation
- 6) Thermal output at layout temperature; tolerance +/- 8 %
- 7) Power consumption of all electrical consumers which are mounted at the module / genset
- 8) Deviations from the layout parameters respectively the reference fuel can have influence on the obtained efficiency and exhaust emissions
- 9) Functional capability
- 10) Reference value at nominal load (without amount of oil exchange)
- 11) Genset max. 1000 m height of location and max. 40 °C intake air temperature; else power derating
- 12) Max. allowable cos phi at nominal power (view of producer)
- 13) Stated values for cooling fluid composition 65% water and 35% glycol, adaption for use of other cooling fluid composition necessary
The system design must consider the tolerance.
- 14) Pressure loss at reference flow rate
- 15) The Cv value declares the volumetric flow in m³/h at a pressure drop of 1 bar. Min. and max. flow rate limits are defined.
- 16) Stated values for pure water, adaption for other cooling fluid composition necessary
- 17) Only generator- and surface losses
- 18) Frost-free conditions must be guaranteed
- 19) Amount of ventilation air must be adapted to the gas safety concept
- 20) Assemblies including pipe work
- 21) All sound pressure levels at nominal load
- 22) Max. admissible cos phi depending on voltage in accordance with the requirements of the BDEW Mittelspannungsrichtlinie (German Medium Voltage Directive)

EDAM / EDAT